

THOMSON  
\*  
DELPHION

RESEARCH

PRODUCTS

INSIDE DELPHION

[Home](#) | [About Us](#) | [Research & Development](#) | [My Account](#) | [Products](#)

 Search: [Quick/Number](#) [Boolean](#) [Advanced](#)

## The Delphion Integrated View

 Get Now: ☒ PDF | [More choices...](#)

 Tools: Add to Work File: [Create new Wor](#)

 View: INPADOC | Jump to: [Top](#)  Go to: [Derwent...](#)
 [Ema](#)

Title: JP11260372A2: MANUFACTURE OF NONAQUEOUS SECONDARY B

Country: JP Japan

Kind: A

 Inventor: FURUKAWA SANEHIRO;  
FUJIMOTO MASAHISA;  
YOSHINAGA NORIYUKI;  
UENO KOJI;

 Assignee: SANYO ELECTRIC CO.LTD  
[News, Profiles, Stocks and More about this company](#)

Published / Filed: 1999-09-24 / 1999-01-14

Application Number: JP1999000008215

 IPC Code: [H01M 4/66](#); [H01M 2/02](#); [H01M 4/02](#); [H01M 10/40](#);

 Priority Number: 1999-01-14 [JP1999019998215](#)

Abstract:

... PROBLEM TO BE SOLVED: To improve the cycle characteristic and load characteristic, while preventing the elution of a collector by constructing a positive electrode collector and/or a positive electrode armor of aluminum with aluminum oxide coating on the surface and having lithium intercalate into a negative electrode material by injecting an electrolyte.

... SOLUTION: A positive electrode collector is constructed of an aluminum foil with the surface covered with aluminum oxide. By mixing petroleum coke with N-methylpyrrolidone solution, in which polyvinylidene fluoride is dissolved, a mixed solution is prepared. Next, by applying this mix solution to a negative electrode collector made of copper foil and then bringing the negative collector into contact with lithium foil, a negative electrode 2 is formed. Lithium on the negative electrode 2 is intercalated into the petroleum coke serving as a negative electrode material after injecting the electrolyte. Then, a separator 3 is arranged between the positive electrode 1 and the negative electrode 2, and these are wound up into a spiral shape and form a group 4 of electrodes.

... COPYRIGHT: (C)1999,JPO


Family: None

Other Abstract Info: DERABS C1999-596408 DERABS C1999-596408



BEST AVAILABLE COPY





[Nominate](#)

[this for the Gallery...](#)

© 1997-2003 Thomson Delphion    [Research Subscriptions](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact](#)

**THOMSON**  
  
**DELPHION**

**RESEARCH**  
[Home](#) | [About Us](#) | [Contact Us](#) | [By Account](#) | [Products](#)


**PRODUCTS**  
[Search: Quick/Number](#) | [Boolean](#) | [Advanced](#)

**INSIDE DELPHION**

## The Delphion Integrated View

Get Now: ☒ PDF | [More choices...](#)

Tools: Add to Work File: [Create new Wor](#)

View: [INPADOC](#) | Jump to: [Top](#)  Go to: [Derwent..](#)

 [Ema](#)



**Title:** JP11260372A2: MANUFACTURE OF NONAQUEOUS SECONDARY B

**Country:** JP Japan

**Kind:** A

**Inventor:** FURUKAWA SANEHIRO;  
FUJIMOTO MASAHIRO;  
YOSHINAGA NORIYUKI;  
UENO KOJI;

**Assignee:** SANYO ELECTRIC CO LTD  
[News, Profiles, Stocks and More about this company](#)

**Published / Filed:** 1999-09-24 / 1999-01-14

**Application** JP1999000008215

**Number:**

**IPC Code:** [H01M 4/66](#); [H01M 2/02](#); [H01M 4/02](#); [H01M 10/40](#);

**Priority Number:** 1999-01-14 [JP1999019998215](#)

**Abstract:**

**PROBLEM TO BE SOLVED:** To improve the cycle characteristic and load characteristic, while preventing the elution of a collector by constructing a positive electrode collector and/or a positive electrode armor of aluminum with aluminum oxide coating on the surface and having lithium intercalate into a negative electrode material by injecting an electrolyte.


**SOLUTION:** A positive electrode collector is constructed of an aluminum foil with the surface covered with aluminum oxide. By mixing petroleum coke with N-methylpyrrolidone solution, in which polyvinylidene fluoride is dissolved, a mixed solution is prepared. Next, by applying this mix solution to a negative electrode collector made of copper foil and then bringing the negative collector into contact with lithium foil, a negative electrode 2 is formed. Lithium on the negative electrode 2 is intercalated into the petroleum coke serving as a negative electrode material after injecting the electrolyte. Then, a separator 3 is arranged between the positive electrode 1 and the negative electrode 2, and these are wound up into a spiral shape and form a group 4 of electrodes.

COPYRIGHT: (C)1999,JPO

**Family:** None

**Other Abstract** DERABS C1999-596408 DERABS C1999-596408  
**Info:**





[Nominate](#)

[this for the Gallery...](#)

© 1997-2003 Thomson Delphion

[Research Subscriptions](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact](#)



(19)

(11) Publication number:

**11**

Generated Document

**PATENT ABSTRACTS OF JAPAN**(21) Application number: **11008215**(51) Intl. Cl.: **H01M 4/66 H01M 2/02 H01M 10/40**(22) Application date: **14.01.99**

(30) Priority:	(71) Applicant: <b>SANYO ELECTRIC CO</b>
(43) Date of application publication: <b>24.09.99</b>	(72) Inventor: <b>FURUKAWA SANEHIRO FUJIMOTO MASAHIRO YOSHINAGA NORIYUK UENO KOJI</b>
(84) Designated contracting states:	(74) Representative:

**(54) MANUFACTURE OF  
NONAQUEOUS  
SECONDARY BATTERY**


(57) Abstract:

**PROBLEM TO BE SOLVED:** To improve the cycle characteristic and load characteristic, while preventing the elution of a collector by constructing a positive electrode collector and/or a positive electrode armor of aluminum with aluminum oxide coating on the surface and having lithium intercalate into a negative electrode material by injecting an electrolyte.

**SOLUTION:** A positive electrode collector is constructed of an aluminum foil with the surface covered with aluminum oxide. By mixing petroleum coke with N-methylpyrrolidone solution, in which polyvinylidene fluoride is dissolved, a mixed solution is prepared. Next, by applying this mix solution to a

negative electrode collector made of copper foil and then bringing the negative collector into contact with lithium foil, a negative electrode 2 is formed. Lithium on the negative electrode 2 is intercalated into the petroleum coke serving as a negative electrode material after injecting the electrolyte. Then, a separator 3 is arranged between the positive electrode 1 and the negative electrode 2, and these are wound up into a spiral shape and form a group 4 of electrodes.

COPYRIGHT: (C)1999,JPO





(19)

(11) Publication number: **11**

Generated Document.

**PATENT ABSTRACTS OF JAPAN**(21) Application number: **11008215**(51) Intl. Cl.: **H01M 4/66 H01M 2/02 H01M 10/40**(22) Application date: **14.01.99**

(30) Priority:	(71) Applicant: <b>SANYO ELECTRIC CO</b>
(43) Date of application publication: <b>24.09.99</b>	(72) Inventor: <b>FURUKAWA SANEHIRO FUJIMOTO MASAHIRO YOSHINAGA NORIYUK UENO KOJI</b>
(84) Designated contracting states:	(74) Representative:

**(54) MANUFACTURE OF  
NONAQUEOUS  
SECONDARY BATTERY**

(57) Abstract:

**PROBLEM TO BE SOLVED:** To improve the cycle characteristic and load characteristic, while preventing the elution of a collector by constructing a positive electrode collector and/or a positive electrode armor of aluminum with aluminum oxide coating on the surface and having lithium intercalate into a negative electrode material by injecting an electrolyte.

**SOLUTION:** A positive electrode collector is constructed of an aluminum foil with the surface covered with aluminum oxide. By mixing petroleum coke with N-methylpyrrolidone solution, in which polyvinylidene fluoride is dissolved, a mixed solution is prepared. Next, by applying this mix solution to a

negative electrode collector made of copper foil and then bringing the negative collector into contact with lithium foil, a negative electrode 2 is formed. Lithium on the negative electrode 2 is intercalated into the petroleum coke serving as a negative electrode material after injecting the electrolyte. Then, a separator 3 is arranged between the positive electrode 1 and the negative electrode 2, and these are wound up into a spiral shape and form a group 4 of electrodes.

COPYRIGHT: (C)1999,JPO

